



# PRIMER 99

## Primer 99

Catalog Number: Y34104

A solution of an amine complex for improving adhesion to concrete

### Product description

A solution of an amine complex.

### Product Uses

It is intended for use as a base layer for Polytar 99H to enhance adhesion to concrete.

### Packaging

16 kg pail



## Method of Use

### Preparing the area

Ensure the surface is clean and free from loose parts, dust, casting skins, concrete crumbs, oil, and any foreign material that may interfere with adhesion. Metal should be cleaned of grease and/or rust.

### Method of application

Primer 99 is intended for brush application without further dilution. The required quantity is 100-200 g/m<sup>2</sup>. When dealing with sealing of contacts, prepare the surface as described in the Polytar 99H product sheet. Wait 1-2 hours for the primer to dry completely (depending on weather conditions). Also, read the Polytar 99H product sheet and follow the instructions, especially regarding surface preparation, material, and application.



### Remarks

- ✓ To prevent the primer from being covered with a layer of dust or damaged by sunlight, it is recommended to cover the primer with the sealing material on the day of primer application.
- ✓ Ventilate enclosed spaces during and after application.
- ✓ Store in a cool, shaded place. Do not store at temperatures below 5 °C.
- ✓ Clean tools immediately after use with mineral turpentine produced by Pazkar.
- ✓ The product is flammable and does not contain hazardous solvents.

### Safety instructions

- ✓ **Not for human consumption.**
- ✓ **Before using the product, you should read the safety instructions and warnings that appear on the product label and the safety data sheet (MSDS) which can be obtained from Pazkar Ltd.**
- ✓ Keep away from heat sources (S15).
- ✓ Keep away from sources of ignition. Smoking is prohibited (S16).
- ✓ Do not inhale the fumes/spray (S23).
- ✓ Avoid contact with skin and eyes (S24/25).
- ✓ Use appropriate protective clothing, gloves, protective glasses / face mask (S36/37/39).
- ✓ During the use of the product, its drying, and the application of other products in its vicinity, ensure the area is ventilated and prevent any sparks or fire until the solvent has completely evaporated.

For Safety detailed instructions please refer to Pazkar's safety data sheets (MSDS)

#### Warranty

Pazkar's products are manufactured to rigid standards of quality. Pazkar makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. Users must always refer to the most recent issue of the local product data publication for the product concerned. The user of the product must test the product's suitability for the intended application and purpose. Due to differences in materials, substrates and site conditions Pazkar assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including but not limited to, the implied warranty of merchantability, fitness for a particular purpose, nor any liability arising from any legal relationship. Subject to our terms and conditions, Pazkar grants a product warranty certificate for specific products, for any further information please contact us at [info@pazkar.co.il](mailto:info@pazkar.co.il). All orders are accepted subject to our current inventory, terms and conditions of sale and delivery.