

# EMOLBIT HF-MS 152

Catalog Number: Y20501

## **EMOLBIT HF-MS 152**

### Bituminous emulsion for the production of cold asphalt.

### **Product description**

MOLBIT HF-MS 152 is a bituminous emulsion of the type High Float.

### **Product Uses**

A bituminous emulsion designed for the production of cold asphalt for aggregation.

### Packaging

190 kg Barrel



### **Advantages**

 Forms a thick film over the aggregate of which the cold asphalt mix is produced.

### Storage

 Store in a dry, shaded place, at temperatures In the range of 5 to 40°C.

# **EMOLBIT HF-MS 152**



## **Technical Specifications**

Property Type	Property	Unit	Required Value	Testing techniques
Emulsified	Saybolt Furol viscosity at 25°c	seconds	Max 50	ASTM D88
	Stability in storage for 24 hours	% in mass	Max 1	ASTM D244
	Screening	% in mass	Max 0.1	ASTM D244
	Residue distillation	% in mass	MIN 55	ASTM D244
In the residue distillation	Permeability at 25°c , 100 gr, 5 seconds	1/10mm	200	ASTM D5
	Ductility at 25°c , 5 cm a minute	cm	MIN 40	ASTM D113
	Solubility at TCE	% in mass	MIN 97.5	ASTM D244

### **Method of Use**

### Remarks

✓ Drying time from spraying is 24 hours.

### Safety instructions

- Not for human consumption
- Before using the product, read the product's safety data sheet (MSDS) available at PAZKAR Ltd.
- When using the material, wear personal protective equipment (appropriate clothing, gloves, protective glasses/ face mask).
- Wash your hands with soap and water immediately after use.

#### For Safety detailed instructions please refer to Pazkar's safety data sheets (MSDS)

#### Warranty

Pazkaps products are manufactured to rigid standards of quality. Pazkar makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. Users must always refer to the most recent issue of the local product data publication for the product concerned. The user of the product must test the products suitability for the intended application and purpose. Due to differences in materials, substrates and site conditions Pazkar assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including but not limited to, the implied warranty of merchantability, fitness for a particular purpose, nor any liability arising from any legal relationship. Subject to our terms and conditions, Pazkar grants a product warranty certificate for specific products, for any further information please contact us at info@pazkar.co.il. All orders are accepted subject to our current inventory, terms and conditions of sale and delivery.



Pazkar Ltd. Alon-Tavor Indastrial Zone, Afula, 1812001, Tel. + 972 4 6423120 infopazkar@pazkar.co.il www.pazkar.co.il