

PAZDRAIN FLT 500

Catalog Number: D85301

PAZDRAIN FLT 500

Flat HDPE/LDPE sheets for protection and substructure

Product description

PAZDRAIN FLT500 is a flat, elastic, highly puncture resistant polyethylene sheet (HDPE/LDPE).

Product Uses

- To protect waterproofing subterranean areas and spaces in vertical and horizontal applications.
- Create a clean and leveled infrastructure as an alternative for lean concrete and preventing capillary rise of water above the ground floor.

Packaging

Roll length, 50 m Roll width, 2 m



Advantages

- Easy and fast installation.
- Prevents damage to the waterproofing system during backfilling and soil compaction.
- Connection of two adjacent sheets using a butyl, double-sided adhesive tape BOOTY BAND.

PAZDRAIN FLT 500



Technical Specifications

Test type	Test tesults	Testing techniques
Sheet width	2.0±3% m	IS 556
Average thickness	500±8% Micron	IS 556
(Tearing strength (Length/Width	70/65 N	IS 878 Section 3
(Tearing Elongation (Length/Width	225/350%	IS 878 Section 3
Visible light transmission	< 5%	
Weight per linear meter	0.96 kg	
Weight per M2	0.48 kg	

Method of Use

Method of application

- ✓ PAZDRAIN FLT500 sheet is easily applied and does not require special experience or skill.
- Sheets can be attached by a designated double sided butyl adhesive tape type BOOTY BAND.
- Cutting the sheet to the required length is done using a sharp knife.
- Connecting the sheet to the walls is done using steel nails and yardsticks above the waterproofing system.

For Safety detailed instructions please refer to Pazkar>s safety sheets (MSDS)

Warranty

Pazkars products are manufactured to rigid standards of quality. Pazkar makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. Users must always refer to the most recent issue of the local product data publication for the product concerned. The user of the product must test the products suitability for the intended application and purpose. Due to differences in materials, substrates and site conditions Pazkar assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including but not limited to, the implied warranty of merchantability, fitness for a particular purpose, nor any liability arising from any legal relationship. Subject to our terms and conditions, Pazkar grants a product warranty certificate for specific products, for any further information please contact us at info@pazkar.co.il. All orders are accepted subject to our current inventory, terms and conditions of sale and delivery.

