

PAZ YAROK

Water-based, environmentally friendly ecological primer for cold application.

Product description

PAZ YAROK is a water-based, environmentally friendly ecological primer for cold application.

Product Uses

PAZ YAROK is a Foundation primer layer applied before applying bituminous membranes, a layer of hot bitumen, bituminous gum and water-based bituminous pastes.

Packaging

Can 15 kg



Advantages

- ✓ Water-based, environmentally friendly ecological primer.
- ✓ Applicable over moist surfaces.
- ✓ Particularly resistant in wet and damp conditions.
- ✓ Suitable for surfaces made of concrete, Betkal, blocks and mortar.

Technical Specifications

Test type	Test results
Appearance	Brown / black emulsion
Capacity for adhesion	Outstanding capacity for adhesion to concrete and BETKAL
Drying time	1-6 hours, (respective of weather conditions).

Method of Use

Surface Preparation

- ✓ Verify that the surface to be waterproofed is clean and clear of loose parts, dust, casting shells, concrete morsels, oil and any other foreign substance that may impact adhesion.
- ✓ Holes should be filled with polymer modified grout. Holes in the concrete may result in bubbles after application, especially in walls exposed to direct sunlight.
- ✓ Protruding concrete parts should be ground to the actual level of the concrete. Protruding concrete may result in material leaking after application.

Method of application

- ✓ May be applied with an airless sprayer, a brush, a roller or a wiper.
- ✓ Mix the material thoroughly and dilute it 1:1 ratio in water.
- ✓ After the dilution, mix the material again until a uniform homogeneous solution is obtained.
- ✓ Apply a uniform coat of 300gr/M².
- ✓ Wait for about 1-6 hours until it is dry to the touch. Waiting time for drying may change according to weather conditions (humidity, temperature, etc.)
- ✓ If the use is intended for a primer before welding bituminous membranes, you must wait for the primer layer to completely dry before starting to weld the membranes in order to prevent bubbles and swelling.



Method of Use

Remarks

- ✓ In order to prevent the primer being covered with a layer of dust or damaged by sun rays, it is recommended to cover the primer with the waterproofing material up to two days after application.
- ✓ We recommend ventilating closed spaces during and following application.
- ✓ Store in a cool, shaded place. Do not store in temperatures under 5°C.
- ✓ Clean tools immediately after use with mineral turpentine made by Pazkar.
- ✓ The product is non-flammable and does not contain hazardous solvents.

Safety instructions

- ✓ **Not for human consumption.**
- ✓ While using the material, wear personal protective equipment (appropriate clothing, gloves, protective glasses / face mask).
- ✓ Wash your hands with soap and water immediately after use.

For Safety detailed instructions please refer to Pazkar's safety data sheets (MSDS)

Warranty

Pazkar's products are manufactured to rigid standards of quality. Pazkar makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. Users must always refer to the most recent issue of the local product data publication for the product concerned. The user of the product must test the product's suitability for the intended application and purpose. Due to differences in materials, substrates and site conditions Pazkar assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including but not limited to, the implied warranty of merchantability, fitness for a particular purpose, nor any liability arising from any legal relationship. Subject to our terms and conditions, Pazkar grants a product warranty certificate for specific products, for any further information please contact us at info@pazkar.co.il. All orders are accepted subject to our current inventory, terms and conditions of sale and delivery.