

POLYPAZ 3/250

Product Description

Polypaz 3/250 is an elastomeric Bitumen-polymer waterproofing membrane (containing SBS) reinforced with non woven spun bond polyester fabric.

Product Uses

- Retarding reflective cracks on asphaltic layers in road **construction and rehabilitation** projects.
- Water barrier in expansive soils for preventing swelling and contracting cycles.
- Waterproofing membrane for parking lots under asphalt layer (with a minimum of 5 cm thickness).

Benefits & Advantages

- High mechanical strength and elongation.
- High resistance to cyclic cracking and puncture.

Technical Properties

Properties	Test Method	Specifications	Tolerances
Thickness, mm	EN 1849-1	3	± 0.3
Tensile strength, LD/TD , N/5cm	EN 12311-1	700/700	-10%
Elongation , LD/TD , %	EN 12311-1	35/35	-5 absolute
Cold Flexibility, °C	EN 1109	-20	
Heat stability, °C	EN 1110	110	

Instructions for use

1. Surface preparation and product installation according to an ad-hoc Pazkar specification.
2. Application temperature should be greater than 5°C, while the formal weather forecast predicts temperature rise in the following days to come.

Packaging

30 rolls per pallet.

Storage

Rolls should be transported and stored in an upright vertical position.

Store the product in a well-ventilated and shadowed place.

Do not place one pallet over the other.

NOTE: Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging.

For specific storage requirements consult Pazkar's representatives.

For safety detailed instructions please refer to Pazkar's safety sheets (MSDS).

Warranty

Pazkar's products are manufactured to rigid standards of quality. Pazkar makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. Users must always refer to the most recent issue of the local product data publication for the product concerned. The user of the product must test the product's suitability for the intended application and purpose. Due to differences in materials, substrates and site conditions Pazkar assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including but not limited to, the implied warranty of merchantability, fitness for a particular purpose, nor any liability arising from any legal relationship.

Subject to our terms and conditions, Pazkar grants a product warranty certificate for specific products, for any further information please contact us at info@pazkar.co.il.

All orders are accepted subject to our current inventory, terms and conditions of sale and delivery.