

TAR PAPER 250

Bituminous sheets used for coating and protection, complies with the requirements of

Product description

Reinforced bituminous mass, strengthened with fabric-like reinforced paper and coated with fine sand on both sides. Complies with the requirements of IS 80.

Product Uses

Protection and coating of wood and concrete roofs, coating subterranean walls and protection of bituminous waterproofing against mechanical damage above and below ground, protection from capillary water.

Packaging

25 Palletted rolls



Advantages

- ✓ High resistance to cyclic cracking.
- ✓ High resistance to asphalt perforation.
- ✓ High mechanical strength.
- ✓ High endurance in subterranean waterproofing
- ✓ Complies with the requirements of NTI (Israel Roads) specifications (table 51.07.02 04) and the general specifications (table 51.08/02).
- ✓ Root resistance according to DIN 4062 standard.

Technical Specifications

Test type	Test results	Testing techniques
Reinforcement	cardboard paper	
Roll length, m	20	
Roll width, m	1	
Longitudinal tensile strength, Newton / 5 cm	> 250	
Lateral tensile strength, Newton / 5 cm	> 200	ASTM D5147
Elongation length %	> 2	ASTM D5147
Elongation width %	> 2	ASTM D5147
Heat resistance, °C	< 80	ASTM D5147

Method of Use

Surface Preparation

Verify that the surface to be waterproofed is clean and clear of loose parts, dust, casting shells, concrete morsels, oil and foreign substances that may impact adhesion.

Method of application

Spread the sheet and bond it with FLEXPАЗ H bituminous mastic or ELASTEX type hot bitumen made by PAZKAR.

Remarks

- ✓ Store in a shaded, dry, ventilated place in temperature over 5°C.
- ✓ Rolls should be stored in a vertical position only.
- ✓ Do not store a pallet over a pallet.

For Safety detailed instructions please refer to Pazkar's safety sheets (MSDS)

Warranty

Pazkar's products are manufactured to rigid standards of quality. Pazkar makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. Users must always refer to the most recent issue of the local product data publication for the product concerned. The user of the product must test the product's suitability for the intended application and purpose. Due to differences in materials, substrates and site conditions Pazkar assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including but not limited to, the implied warranty of merchantability, fitness for a particular purpose, nor any liability arising from any legal relationship. Subject to our terms and conditions, Pazkar grants a product warranty certificate for specific products, for any further information please contact us at info@pazkar.co.il. All orders are accepted subject to our current inventory, terms and conditions of sale and delivery.