



# UNIVERSAL PRIMER

## Universal Primer

Catalog Number: Y33001

Cold-application bituminous foundation solution

### Product description

Universal Primer is a cold-application bituminous foundation solution based on solvents.

### Product Uses

Universal Primer serves as a base layer before the application of bituminous membranes, blown bitumens, mastics, and bituminous pastes based on solvents. Suitable for application with excellent adhesion capacity on concrete, asbestos, and metal surfaces.

### Packaging

15 kg pail



## Technical Specifications

Test type	Test results
Appearance	Black solution
Viscosity	25-125 seconds
Water Content	None
Volatile Distillation	to 225 °c - 35% min. to 360 °c - 65% min.
Adhesion Capacity	Excellent to concrete, asbestos, and metal
Drying Time	1 to 6 hours (depending on weather conditions)

## Method of Use

### Preparing the area

Ensure the surface to be sealed is clean and free from loose parts, dust, casting peels, concrete debris, oil, and any foreign material that may interfere with adhesion. Fill holes with polymer-enhanced cementitious filler. Holes in concrete may cause bubbles after application, especially on roofs and walls exposed to direct sunlight. Protruding concrete parts should be sawed off to the concrete level itself. Concrete protrusions may cause material leakage after application.

### Method of application

Can be applied using an airless sprayer, brush, roller, or a wiper.

Apply a uniform layer at a rate of about 300 g/m<sup>2</sup>.

Wait about 1-6 hours for touch dry. Drying time may vary according to weather conditions (humidity, temperature, etc.).



## Method of use - continued

### Remarks

- ✓ To prevent the primer from being covered with a layer of dust or damaged by sunlight, it is recommended to cover the primer with the sealing material on the day of application.
- ✓ During the application of the product, its drying, and the application of other products nearby, ensure the area is well-ventilated.
- ✓ Before performing any work with open flames or actions that may generate sparks, ensure that the material is completely dry, the area is ventilated, and it does not contain any vapors from the material.
- ✓ Store the product in a shaded and well-ventilated area. Do not store at temperatures below 5 °C.
- ✓ It is recommended to clean the tools with mineral turpentine produced by Pazkar.
- ✓ The product contains volatile and flammable solvents.

### Safety instructions

- ✓ **Not for human consumption.**
- ✓ **Before using the product, you should read the safety instructions and warnings that appear on the product label and the safety data sheet (MSDS) which can be obtained from Pazkar Ltd.**
- ✓ Keep away from heat sources (S15).
- ✓ Keep away from sources of ignition. Smoking is prohibited (S16).
- ✓ Use appropriate protective clothing, gloves, protective glasses / face mask (S36/37/39).
- ✓ Avoid release into the environment: refer to the special instructions and the Material Safety Data Sheet (S61).

For Safety detailed instructions please refer to Pazkar's safety data sheets (MSDS)

#### Warranty

Pazkar's products are manufactured to rigid standards of quality. Pazkar makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. Users must always refer to the most recent issue of the local product data publication for the product concerned. The user of the product must test the product's suitability for the intended application and purpose. Due to differences in materials, substrates and site conditions Pazkar assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including but not limited to, the implied warranty of merchantability, fitness for a particular purpose, nor any liability arising from any legal relationship. Subject to our terms and conditions, Pazkar grants a product warranty certificate for specific products, for any further information please contact us at [info@pazkar.co.il](mailto:info@pazkar.co.il). All orders are accepted subject to our current inventory, terms and conditions of sale and delivery.